



\*\* INCOMING PART WILL BE CHECK. IT WILL RETURN IF NOT PASS \*\*

|           |          |                                   |                                  |
|-----------|----------|-----------------------------------|----------------------------------|
| POLISHING | GRINDING | NORMAL MACHINING (SMOOTH SURFACE) | NORMAL MACHINING (ROUGH SURFACE) |
| ▽▽▽       | ▽▽       | ▽                                 | ▽                                |

|  |                        |   |                        |                                  |
|--|------------------------|---|------------------------|----------------------------------|
| 1  | DRIVE SPROCKET 20B Z23 | 1   | S 45 C                 | TEETH SURFACE HARDENED 35-40 HRC |
| POS  | DESCRIPTION            | QTY   | MATERIAL               | REMARKS                          |
| FILE DIR: F:\WORK\PT SIAM INDO CONCRETE PRODUCT\project\Tilting 3\Chain Conveyor |                        | SCALE: 1:5  |                        | ASSY NO.                         |
| DIM: mm  |                        | MECHANICAL ENGINEERING SECTION                                |                        |                                  |
| DESIGN   | USER                   | TITLE   |                        |                                  |
| CHECK  | YESSIKO                | <h2 style="text-align: center;">DRIVE SPROCKET TILTING 3</h2> |                        |                                  |
| APRV   | M.NUGRAHA              |   |                        |                                  |
| ( ) = GENERAL TOLERANSI ±0.2% x DIMENSION<br>REFF DWG NO.                        |                        |   |                        |                                  |
| PT SCG LIGHTWEIGHT CONCRETE INDONESIA  |                        | A4  | 2012-DWG-PC-M-00265-10 | REV NO. PAGE                     |
|  |                        |   |                        | 1                                |