



PT. MAKMUR TRITAMA SELARAS INDONESIA

General Contractor, Engineering, Supplier, Trading & HVAC Specialist
(Sales, Service, Repair, Spare Part, Installation, Overhaul, Preventive Maintenance)

Karawang, 02 Agustus 2022

Nomor : 037/MTSI-KRW/08/2022/ST

Hal : Penawaran Harga

Kepada Yth ;
PT. SCG Lightweight Concrete Indonesia
Jl. Surya tekno kav. I-T1-3 Surya cipta kawrawang barat 41361
Tlp. 0267 - 8610362
Up : Bapak Diki Setiadi

Dengan hormat,
Melanjutkan permintaan Bapak, maka berikut ini kami sampaikan Penawaran Harga, dengan rincian sebagai berikut :

PENGECEKAN & PERBAIKAN AC PANEL

No	Description	Unit	Qty	Unit Price	Total Price
1	Jasa Pekerjaan, Include : Service	Lot	1	7.500.000	7.500.000
	Pengecekan Amp				
	Pengecekan Fan In & Fan Out				
	Pengecekan PCB & Wiring				
	Pengecekan Condensor & Evaporator				
	Pengecekan Kebocoran				
	Pengecekan Compressor & Relay				
	Pengecekan Converter PCB & Thermistor				
	Pengecekan Filter, Cappacitor & OLR				
	Pengecekan Temperature				
	Cleaning Overhaul				
	Pengecekan relay & Electrical				
	Test Running & Setting Temp.				
				Total	7.500.000

Rp. 6.500.000,-

Catatan :

- Harga diatas tidak Termasuk PPN 11%
- Cara pembayaran : 30 Hari setelah Invoice diterima
- Validitas Penawaran : 14 Hari

Confirm with
P. Sutrisno by pawan
02/08

Demikian penawaran ini kami ajukan, sambil menunggu kabar baik dari Bapak atas perhatian dan kerjasamanya kami ucapkan terima kasih.

Hormat kami,
PT. Makmur Tritama Selaras Indonesia



Sutrisno
HP : 0856 9255 9952

SK 3310740

Enclosure Cooling Unit
Schaltschrank - Kühlgerät
Climatiseur pour armoires electriques



Spannungsbereich / Frequenzbereich 400 V / 50 Hz
Voltage Range / Frequency Range 480 V / 60 Hz

Rated Voltage	400 V / 50 Hz / 3~	480 V / 60 Hz / 3~
Bemessungsspannung		
Rated Current	3,5 A	3,7 A
Bemessungsstrom		
Starting Current	13,0 A	14,0 A
Anlaufstrom		
Circuit Breaker	6,3-10 A	6,3-10 A
Leistungsschalter		
Nominal Capacity	L35 L35 1130 W	L35 L35 1450 W
Bemessungsaufnahme	L35 L50 1400 W	L35 L50 1750 W
Useful Cooling Output	L35 L35 2500 W	L35 L35 2500 W
Nutzkühlleistung DIN 3168	L35 L50 1760 W	L35 L50 1800 W
Temperature Range	20 °C - 55 °C	20 °C - 55 °C
Temperaturbereich		
Refrigerant Charge	R134a, 1175 g (41 oz), Fluid Group 2	
Kältemittel, Füllgewicht		
Allowable Pressure (PS)	HP 435 ps, LP 232 ps	
zul. Druck (PS)	HO 30 bar, NO 16 bar	
Noise Level / Geräuschpegel	73 dB(A)	
IP Code / Schutzart EN 60529		
Int. Circuit / Innenkreislauf	IP 54	
Ext. Circuit / Außenkreislauf	IP 34	
Weight / Gewicht	72 kg	
Date / Datum	18.03.2013	
Production No. / Fabr.-Nr.	D 302243	

ISO 9001 / 14001 certified / **1** package tested EN 379-2
 Approved component / **1** certified gas-unit

Maintains the environmental integrity of Type A3
 hermetic sealed / hermetisch gasdicht
 Contains fluorinated greenhouse gas according to Kyoto Protocol
 Entspricht dem Kyoto-Protokoll betreffend Fluorchlorkohlensäure



WITTEN GmbH, Service Center
 WITTEN GmbH, Service Center
 WITTEN GmbH, Service Center
 WITTEN GmbH, Service Center



