





















Department : Production
 Division : Maintenance

Display Purchase Req. 1021011700



Document Overview On     Personal Setting

2010 PR frm MRP/CBP 1021011700

Header





                Default Values

Requisition Date	St...	Item	A	I	M	Short Text	Quantity	Unit	Delivery Date	P...	Requisitioner	Matl Group	Plant	Stor. ...	Purch. Grp	Total Value
01.03.2022		10 K				PLC Siemens 6ES7138-4DB03-0AB0 Interface	1	PC	09.08.2022	1	Taufik	Supplies	PT SLCI		DBA	6,170,000

Item [10] PLC Siemens 6ES7138-4DB03-0AB0 Inte...  

Material Data | Quantities/Dates | Valuation | Account Assignment | Source of Supply | Status | Contact Person | Texts | Delivery Address | Spec2000 / SC

Item Texts A...

-  Item text
-  Item note
-  Delivery text
-  Material PO text

Purpose : Replacement WKB Controller Modul Network due to lifetime

GL : 523073
 CC : 2011-10000

SIMATIC DP, Electronics module for ET 200S, 1 SSI 25 bit/1 MHz 15 mm width, Module for connection of absolute value encoders with SSI Synchronous Serial Interface with DI and comparison value with clock synchronization



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	40 mA
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
24 V encoder supply	
• 24 V	Yes
• Short-circuit protection	Yes
• Output current, max.	500 mA
Absolute encoder (SSI) encoder supply	
• Absolute encoder (SSI)	Yes
• Type of output voltage	L+ (-0.8 V)
• Short-circuit protection	Yes

• Output current, max.	500 mA
Power loss	
Power loss, typ.	1 W
Hardware configuration	
Module exchange	
• Module exchange during operation of the IM-DP	Yes
• Module exchange under process voltage	Yes
Digital inputs	
Number of digital inputs	1
Input voltage	
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V
Input current	
• for signal "0", max. (permissible quiescent current)	2 mA
• for signal "1", typ.	9 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	300 µs
— at "1" to "0", max.	300 µs
Cable length	
• shielded, max.	50 m
Encoder	
Number of connectable encoders, max.	1
Connectable encoders	
• Absolute encoder (SSI)	Yes
• 2-wire sensor	Yes; Type 2
Encoder signals, absolute encoder (SSI)	
• Input signal	to RS-422
• Telegram length, parameterizable	13, 14, 16, 21, 24 & 25 bit
• Binary code	Yes
• Gray code	Yes
• Cable length, shielded, max.	320 m; At 125 kHz
• Monoflop time	16/32/48/64 µs
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Status indicator forward counting (green)	Yes

- Status indicator backward counting (green)

Yes

Potential separation

Potential separation digital inputs

- Potential separation digital inputs

No; same potential with L+ and SSI

Potential separation counter

- between the channels and backplane bus
- Between the channels and load voltage L+

Yes

No

Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

Weights

Weight, approx.

40 g

last modified:

12/09/2020



PT. VIKTORI PROFINDO ELEKTRIKA

Industrial Engineering Solution (Since 2005)
(Electrical, Mechanical, Instrumentation, Automation and Control System)

JL. Kapuk Timur Blok F23 No. 20F
Delta Silicone 3 Lippo Cikarang
Bekasi - Jawa Barat
Kode Pos 17550

Tel.: +62 21 89911476 - 1480 (Hunting)
Fax.: +62 21 89911474 - 1475
Email: sales@viktori-profindo.com
Website: www.viktori-profindo.com

Q U O T A T I O N

TO : SCG Lightweight Concrete Indonesia, PT.
ATTN : Mr Diki Setiadi
DATE : 04-Feb-2022
OUR REF : QTN-VPE22020041
PAGE NO :

THANK YOU VERY MUCH FOR YOUR REQUEST AND WE PLEASED TO QUOTE AS FOLLOW:

No.	DESCRIPTION	QTY	Price/ea	AMOUNT	Delivery Time
1	6ES7134-4FB01-0AB0 SIMATIC DP, Electronics module for ET 200S, 2 AI Standard U 15 mm width, +/-10V; 13 bit+sign +/-5 V; 12 bit+sign, 1..5 V; 12-bit Cycle time 65 ms/channel with SF LED (group fault)	1 Pcs	3.860.000,00	3.860.000,00	26 weeks
2	6ES7138-4DB03-0AB0 SIMATIC DP, Electronics module for ET 200S, 1 SSI 25 bit/1 MHz 15 mm width, Module for connection of absolute value encoders with SSI Synchronous Serial Interface with DI and comparison value with clock synchronization	1 Pcs	6.170.000,00	6.170.000,00	26 weeks
TOTAL AMOUNT, EXCLUDE PPN			IDR	10.030.000,00	

PAYMENT : TT in Advance

DELIVERY TERM : Franco Karawang

VALIDITY : 7 Days

NOTE : The offered prices are strictly subject to the quantities offered. In case of order, please put our ref number in your PO.

Due to Corona virus out break, delivery could be delayed from estimated time as factory from around the world is reducing people in work space (Social Distancing)

Due to heavy currency fluctuation, our quotation might not valid and subject to cancellation.

WE HOPE OUR QUOTATION IS ACCEPTABLE AND WE ARE PLEASED TO RECEIVE YOUR ORDER

BEST REGARDS,

Lusiana

0817-6876210

Checked By,

Hendrik

0815-1696241

Acknowledge,

Filia Irbanda

PT. VIKTORI PROFINDO ELEKTRIKA
0811-1113089